

MATERIAL SAFETY DATA SHEET

Section 1 – Production Identification and Company Information

Trade Names: Frac Sand and Concrete Sand

Common Names: Silica Sand

Product Use: Frac Sands, Resin Coating Base Sands, Glass Sands, Filtration Media, Glass Sands, Industrial Sands, Grinding Media, Recreational and Agricultural Sands.

Manufacturer's Name: Sierra Frac Sand, LLC
1155 E. Johnson St.
Tatum, TX 75691

Manufacturer's Phone: (903)836-4642

Manufacturer's Fax: (903)836-4643

Section 2 – Hazards Identification

Emergency Overview

Sierra Sand is a gold, light buff to white sand with no odor. It is not flammable, combustible, or explosive. It can cause irritation to the eyes. A single exposure will not result in serious adverse health effects. Crystalline silica is not known to be an environmental hazard.

Potential Health Effects

Inhalation:

- a. Silicosis: Respirable crystalline silica (quartz) can cause chronic silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

- b. Cancer: Crystalline silica (quartz) inhaled from occupational sources in sufficient concentrations is classified as carcinogenic to humans. In its **Ninth Annual Report on Carcinogens**, the National Toxicology Program (NTP) listed crystalline silica as a known human carcinogen, based on sufficient evidence of carcinogenicity from studies in humans indicating a casual relationship between exposures to respirable crystalline silica dust. The International Agency for Research on Cancer (IARC) has evaluated crystalline silica and determined that "crystalline silica inhaled in the form quartz or cristobalite from occupational sources is carcinogen to humans (Group 1)."

- c. Autoimmune Diseases: There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders, -- scleroderma, systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys.
- d. Tuberculosis: Silicosis increases the risk of tuberculosis.
- e. Nephrotoxicity: There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of kidney diseases, including end stage renal disease.

Eye Contact: Crystalline Silica (quartz) may cause abrasion of the cornea.

Skin Contact: May cause abrasion skin

Ingestion: No known health effect.

Acute Effects: One form of silicosis, Acute Silicosis, can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Chronic Effects: The adverse health effects – lung disease, silicosis, cancer, autoimmune disease, tuberculosis, and nephrotoxicity – are chronic effects.

Signs and Symptoms of Exposure: There are generally no signs or symptoms of exposure to crystalline silica (quartz). Often, chronic silicosis has no symptoms. The symptoms of chronic silicosis, if present, are shortness of breath, wheezing, cough and sputum production. The symptoms of acute silicosis are the same as those associated with chronic silicosis; additionally, weight loss and fever may also occur. The symptoms of scleroderma include thickening and stiffness of the skin, particularly in the fingers, shortness of breath, difficulty swallowing and joint problems.

Medical Conditions Generally Aggravated by Exposure: The condition of individuals with lung disease (e.g., bronchitis, emphysema, chronic pulmonary disease) can be aggravated by exposure.

See Section 11, Toxicological Information, for additional detail on potential adverse health effects.

Section 3 – Composition and Information on Ingredients

Hazardous Ingredients

| | |
|-------------------|----------------------------------|
| Name: | Silica, Quartz, SiO ₂ |
| CAS Number: | 14808-60-7 |
| Concentration (%) | 89.0-99.9% |

Section 4 – First Aid Procedures

Inhalation – There is not specific treatment because the health effects associated with silica are chronic. If gross inhalation of silica occurs, remove the person to fresh air, perform artificial respiration as needed, and obtain medical attention as needed.

Eye – Wash the eye with water immediately. If irritation persists, seek medical attention.

Skin – Not Applicable

Ingestion – Not Applicable

Section 5 – Fire Fighting Measures

Crystalline Silica (quartz) is not flammable, combustible, or explosive.

| | |
|------------------------------------|--|
| Flashpoint: | None |
| Upper/Lower Explosive Limit: | Not Combustible |
| Autoignition Temperature: | None |
| Unusual Fire and Explosion Habits: | None |
| Extinguishing Media: | Compatible with all media; use the medium appropriate to the surrounding fire. |
| Special Fire Fighting Procedures: | None with respect to this product |
| Hazardous Combustion Products: | None |

Section 6 – Accidental Release Measures

Wear appropriate personal protective equipment as described in Section 8 of this document. Collect the material using a method that does not produce dust [High-Efficiency Particulate Air (HEPA) vacuum or thoroughly wetting down the silica]. Place the silica in a covered container appropriate for disposal. Dispose of the silica according to federal, state, and local regulations.

Section 7 – Handling and Storage

This product is not to be used for abrasive blasting. Do not breathe dust, which may be created during the handling of this product. Do not rely on vision to determine whether respirable silica is present in the air, as it may be present without a visible cloud. Use good housekeeping procedures to prevent the accumulation of silica dust in the workplace. Avoid the creation of respirable dust.

Use adequate ventilation and dust collection equipment. Ensure that the dust collection system is adequate to reduce airborne dust levels to below the appropriate occupational health limit. Use respiratory protection during the establishment of engineering controls. Refer to Section 8 I Exposure Controls/Personal Protection for further information.

In accordance with the U.S. Occupational Safety and Health Administration's (OSHA) Hazard Communication Standard (29 CFR 1910.1200, 1915.99, 1917.28, 1918.90, 1926.59, 1928.21), state, and/or local right-to-know laws and regulations, familiarize your employees with this MSDS and the information contained herein. Warn your employees (and your customers in case of

resale) of the potential health risks associated with the use of this product and train them in the appropriate use of personal protective equipment and engineering controls, which will reduce their risks of exposure.

See also ASTM International standard practice E 1132-06, "Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica."

Crystalline silica is listed by the Governor of the State of California, under Proposition 65, as requiring the following warning: "Detectable amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in this product."

Section 8 - Exposure Controls/Personal Protection

Exposure Limits (respirable fraction) in Air:

| | | |
|-----------|-------------------------|-------------------------------|
| OSHA-PEL | 10mg/m ³ | (8-HR. Time Weighted Average) |
| | %SiO ₂ +2 | |
| ASGIH-TLV | 0.025 mg/m ³ | (8-HR. Time Weighted Average) |
| NIOSH-REL | 0.05 mg/m ³ | (8-HR. Time Weighted Average) |

Exposure Limits refer to the respirable fraction

Silica is classified as hazardous under Occupational Safety and Health Administration (OSHA) regulations (29 CFR 1910.1200)

CAUTION:

Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870deg.C (1598 deg.F) it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470 deg.C (2678 deg.F), it can change to a form of crystalline silica known as cristobalite. Crystalline silica as trydimite and cristobalite are more fibrogenic than crystalline silica as quartz. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half the PEL for crystalline silica (quartz); the ACGIH TLV for crystalline silica as cristobalite is equal to the TLV for crystalline silica as quartz. THE ACGIH, in 2005, has withdrawn the TLV for crystalline silica as trydimite.

Ventilation: Use local exhaust as required to maintain exposures below the occupational exposure limits; see also ACGIH, Industrial Ventilation – Recommended Practice (latest edition).

Respiratory Protection: This product is not to be used for abrasive blasting. Consult with OSHA regulations and NIOSH recommendations to determine the appropriate respiratory protection during use of this product. Use only NIOSH-approved respiratory protection equipment. Avoid breathing dust produced during the use and handling of this product. If the workplace airborne crystalline silica concentration is unknown for a given task, conduct air monitoring to determine the appropriate level of respiratory protection. Consult with a certified Industrial hygienist, your insurance risk manager, or the OSHA Consultative Services group for detailed information. Ensure appropriate respirators are worn during and following the task, including clean up or whenever airborne dust is present to ensure worker exposures remain below occupational health limits. Provisions should be

made for respiratory protection training program (see 29 CFR 1910.134 – Respiratory Protection for minimum program requirements). See also ANSI standard Z88.2 (latest version) "American National Standard for Respiratory Protection," 29 CFR 1910.134 and 1926.103, and 42 CFR 84.

Gloves: Recommended in situations where abrasion from sand may occur.

Eye: Use protection as appropriate for the task at hand

Other: Use protective clothing as appropriate for the work environment.

Section 9 – Physical and Chemical Properties

Appearance: Gold, Light Buff to White Sand
Odor: None
Physical State: Granular Solid
pH: Not Applicable
Vapor Pressure: Not Applicable
Vapor Density: Not Applicable
Boiling Point or Range, deg.F: 2230 deg.C (4046 deg.F) for Quartz
Melting Point or Range, deg.F: 1710 deg.C (3110 deg.F) for Quartz
Solubility in Water: Insoluble
Specific Gravity: 2.65 (Quartz)

Section 10 – Stability and Reactivity

Stability: Stable
Materials to Avoid: Strong Oxidizing Agents, such as fluorine, chlorine, trifluoride, hydrogen fluoride, and oxygen difluoride.
Hazardous Decomposition Products: Silica will dissolve in hydrofluoric acid and produce a corrosive gas – silicon tetrafluoride.
Hazardous Polymerization: Will not occur

Section 11 – Toxicological Information

A. SILICOSIS

The major concern is silicosis (lung disease), caused by the inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms, chronic, (or ordinary, accelerated, or acute.

Chronic or Ordinary Silicosis is the most common form of silicosis, and can occur after many years of exposure to levels above the occupational exposure limits for airborne respirable crystalline silica dust. It is further defined as either simple or complicated silicosis.

Simple Silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF).

Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than (1) centimeter in diameter. Although there may be no symptoms associated with complicated silicosis or PMF, the symptoms, if present, are shortness of breathe, wheezing, cough and sputum production. Complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease (cor pumonale) secondary to the lung disease.

Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five (5) years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

B. CANCER

IARC – The international Agency for Research on Cancer (“IARC”) concluded that there was “*sufficient evidence* in humans for the carcinogenicity of crystalline silica in the forms of quartz or cristobalite from occupational sources”, and that there is “*sufficient evidence* in experimental animals for the carcinogenicity of quartz and cristobalite.” The overall IARC evaluation was that “crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is *carcinogenic to humans (Group 1)*.” The IARC evaluation noted that not all industrial circumstances studied evidenced carcinogenicity. The monograph also stated that “Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors of affecting its biological activity or distribution of its polymorphs.” For further information on the IARC evaluation, see IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68, “Silica, Some Silicates....” (1997).

NTP – The National Toxicology Program, in its Ninth Annual Report on Carcinogens, concluded that respirable crystalline silica is known to be a human carcinogen, based on sufficient evidence of carcinogenicity from studies in humans indicating a casual relationship between exposure to respirable crystalline silica and increased lung cancer rates in workers exposed to crystalline silica dust.

OSHA – Not regulated as a carcinogen.

There have been many articles published on the carcinogenicity of crystalline silica, which the reader should consult for additional information; the following are examples of published articles:

- (1) “Lung cancer among industrial sand workers exposed to crystalline silica”, *Am J Epidemiol*, (153) 695-703 (2001);
- (2) “Crystalline Silica and the risk of lung cancer in the potteries”, *Occup Environmental Med*, (55) 779-785 (1998);
- (3) “Is Silicosis Required for Silica-Associated Lung Cancer?”, *American Journal of Industrial Medicine*, (37) 252-259 (2000);
- (4) “Silica, Silicosis, and Lung Cancer: A Risk Assessment”, *American Journal Of Industrial Medicine*, (38) 8-18 (2000);

- (5) "Silica, Silicosis, and Lung Cancer: A Response to a Recent Working Group Report", *Journal of Occupational and Environmental Medicine*, (42) 704-720 (2000).

(C) AUTOIMMUNE DISEASES

There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders, --scleroderma, systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. For a review of the subject, the following may be consulted: "Occupational Exposure to Crystalline Silica and Autoimmune Disease", *Environmental Health Perspectives*, (107) Supplement 5, 793-802 (1999); "Occupational Scleroderma", *Current Opinion in Rheumatology*, (11) 490-494 (1999); "Connective tissue disease and silicosis", *Am J Ind Med*, (35), 375-381 (1999).

(D) TUBERCULOSIS

Individuals with silicosis are at increased risk to develop pulmonary tuberculosis, if exposed to persons with tuberculosis. The following may be consulted for further information: *Occupational Lung Disorders*, Third Edition, Chapter 12, entitled "Silicosis and Related Diseases", Parkes, W. Raymond (1994); "Risk of pulmonary tuberculosis relative to silicosis and exposure to silica dust in South African gold miners," *Occup Environ Med*, (55) 496-502 (1998); "Occupational risk factors for developing tuberculosis," *Am J Ind Med*, (30) 148-154 (1996).

(E) KIDNEY DISEASE

There is evidence that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis is associated with the increased incidence of kidney diseases, including end stage renal disease. For additional information on the subject, the following may be consulted: "Kidney Disease and Silicosis", *Nephron*, (85) 14-19 (2000); "End stage renal disease among ceramic workers exposed to silica", *Occup Environ Med*, (56) 559-561 (1999); "Kidney disease and arthritis in a cohort study of workers exposed to silica", *Epidemiology*, (12) 405-412 (2001).

(F) NON-MALIGNANT RESPIRATORY DISEASES

NIOSH has cited the results of studies that report an association between dusts found in various mining operations and non-malignant respiratory disease, particularly among smokers, including bronchitis, emphysema, and small airways disease. The results were not conclusive regarding an association among those with silicosis, only smokers, or the result of general mineral dust that does not contain silica. See NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica, published in April 2002, available from NIOSH, 4676 Columbia Parkway, Cincinnati, OH 45226, or at <http://www.cdc.gov/niosh/02-129A.html>.

Section 12 – Ecological Information

Crystalline silica is not known to be ecotoxic.

Section 13 – Disposal Considerations

General: Crystalline silica may be land filled. Material should be placed in covered containers to minimize generation of airborne dust.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR 261.

The above information applies to Sierra Frac Sand, LLC only as sold. The product may be contaminated during use, and it is the responsibility of the user to assess the appropriate disposal method in this situation.

Section 14 – Transport Information

Crystalline silica (quartz) is not a hazardous material for purposes of transportation under the U.S. Department of Transportation of Hazardous Materials, 49 CFR 172.101.

Section 15 – Regulatory Information

UNITED STATES (FEDERAL AND STATE)

TSCA No.: Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR 261 *et seq.*

CERCLA: Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.

Emergency Planning and Community Right to Know Act: Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirement of Section 313.

Clean Air Act: Crystalline silica (quartz) processed by Sierra Frac Sand, LLC. was not processed with or does not contain and Class I or Class II ozone depleting substances.

FDA: Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR 175.300(b)(3)(xxvi).

NTP: Respirable crystalline silica (quartz) is classified as a known carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

California Proposition 65: Crystalline silica (quartz) is classified as a substance known to the state of California to be a carcinogen.

California Inhalation Reference Exposure Limit (REL): The California chronic REL for respirable crystalline silica is 3 ug/m³. A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

Massachusetts Toxic Use Reduction Act: Respirable crystalline silica is considered toxic per the Massachusetts Toxic Use Reduction Act.

Pennsylvania Worker and Community Right to Know Act: Quartz is considered hazardous for purposes of the Act, but it is not a special hazardous substance or an environmental hazardous substance.